

ACID CLEANER

Cleaning agent for tiles and grout

Description

It is an acid new generation cleaning agent for tiles and grout, consisting of an innovative combination of active and powerful cleaners. It drastically removes any kind of cement, plaster or lime remains as well as grouts, paints and other stains (including oil, beverages, etc).

Restrictions

The product is not suitable for cleaning decorative tiles, marble, brick, limestone and sanitary fixtures.

Technical Specifications

Form: liquid - transparent.

Density: $\approx 1,0$ kg/L.

Consumption: $\approx 4,0$ m²/L

PH: < 1

Contains: Phosphoric acid, anionic surfactants: $\leq 5\%$

Application temperature: +5 °C to +40 °C

Instructions for use

1. In case the installation is in a closed area open the doors and windows to prevent vapor accumulation.
2. The cleaner is applied undiluted to the surface to be cleaned.
3. Then scrub with a stiff broom or brush, leaving it on for about 2-3 minutes.
4. Then rinse with plenty of water to remove any cleaning residue. In case of persistent stains, repeat the procedure.
5. Follow the same procedure when cleaning grouts. It is important to note that grouts should be left to set for at least 15 days.
6. It is recommended to test it on a small part of the surface. first

Storage

Preferably in sheltered areas, locked and away from children, protected from the sun, for at least 36 months from the production date.

Packages

Plastic containers of 1L and 5L.

Precautions and safety

It is recommended to be kept locked and away from children. The product is highly corrosive and irritant. Wear protective gloves, clothing, goggles and face protection, as well as any other standard precaution measures applicable when using chemicals. In case of eye or skin contact, immediately wash with plenty of water by continuous rinse and seek medical advice. For more information, please refer to the material safety data sheet as well as the instructions for safe use on the product packaging. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Notes

Technical data, properties, recommendations and information on BAUER products are supplied in good faith. They are based on the company's research and experience, provided that they are stored and applied under normal conditions. Given that in each case of application, the use of the materials and the conditions of the project as well as the overall environment, cannot be controlled by the company, the sole responsibility for the result lies with the end user of the product. No liability under any legal relationship can be established against the company, based on the information listed within this document. The present edition of this Technical Data Sheet automatically cancels any previous editions. The end user of the products should always refer to the latest Technical Data Sheet version.

Other information

BAUER BUILDING TECHNOLOGIES

Megara Industrial Estate, Attica

Tel: +30 210 5744222

Fax: +30210 5740777

Email: info@netbauer.com

[http// www.netbauer.com](http://www.netbauer.com)

Frankfurt, Reg. No 312310 QM

Qualitätsmanagementsystem und No 312310 UM

Umweltmanagementsystem

Zertifiziert nach DIN EN ISO 9001 und EN ISO 14001

